

Master Care

For lacquered, vinyl/LVT and laminate floors

Technical Data Sheet 09.02.2021 - p. 1/2

Care for your vinyl floor, laminate floor or lacquered wood floor using Master Care. This care product smoothens small scratches, increases the resistance of the surface and provides effective protection against wear. This extends the lifetime of the surface or floor. Because Master Care does not build up a thick coating, you can use the product whenever it is required.



- · Care treatment to refresh floors
- Extends the lifetime of the floor
- Protects against wear and scratches
- · Easy to use
- IBR-certified

Application area

For all types of vinyl, laminate, PVC and lacquered/painted surfaces.

Work description

Preparation Wash the floor thoroughly with WOCA Intensive Wood Cleaner, until the surface is perfectly clean.

Wash with clean water afterwards. Leave the floor to dry completely before application of Master Care.

Always remember to test on a less visible spot to check the compatibility of the surface with the

product.

Treatment Shake the container well before use.

Apply the concentrated care product as a thin, even coat. If the cloth/mop becomes dirty, rinse in clean water and wring thoroughly. Then continue the application. Do not apply additional Master Care

once a surface has begun to dry.

Leave the floor to dry for approximately 30-60 minutes or until it is completely dry before use. No

polishing or other treatment is required afterwards.

Note For best results, use WOCA Master Cleaner for regular cleaning of the treated surface.

Drying time

Drying time Approx. 60 minutes.



Declaration Triisobutylphosphate. Can trigger allergic reaction.

Density Approx. 1.01 g/ml

pH-value 7.2-8.2 Shelf life 24M

Application Temperature + 15-30°C

Coverage Approx. 60 m²/L, depending on wood type and surface.

Mixing ratio Undiluted.

Storage +10-25°C. Keep out of reach of children. Do not expose to

heat (e.g. sunlight). Store frost-free during winter and cool

during summer.

VOC VOC-Max: 30 g/l, MAXIMUM VOC CONTENT (A/i (WB)):

140 g/l.

Packaging 1L

Migration_Test EN 71-3:2013

Authorisations Danish Indoor Climate Labelling

IBR: TVOC28/A+, AgBB Z-157.10-198

Re-treatment 2 times a year

Maintenance and related products

Weekly cleaning Master Cleaner, #684510

Related products Intensive Wood Cleaner, #551525

Application tools Lacquer Application Roller, 11 mm luv, #88003

Wool Pad, #596051 Blue pad holder, #399710

Contact

WOCA Denmark A/S

Tværvej 6

DK - 6640 Lunderskov T +45 9958 5600

info@wocadenmark.com wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.